Technical Datasheet

| Article - No: | PG-QA-R025-01-0060 Revision: A0 |
|--------------------------|--|
| Remarks | single use only |
| Specification | |
| Product name | UFPT-F-50, 50uL filter tips |
| Production conditions | Class 100,000 clean room production |
| | No release agent is used |
| | Motor molding |
| Classification | CE/IVD |
| Dimensions | C 50.5±0.2 D 21.00±0.4 E 16.0±0.1 F G Φ6.30 Φ7.4±0.05 |
| Colour | Cear |
| Graduation | moulded rings |
| Nominal Capacity | 1-50UL |
| Material Characteristics | polypropylene(PP),premium surface |
| | filter: high density polyethylene(PE) |
| Product Characteristics | biologically inert |
| | physiologically harmless |
| | no heavy metals according to EC/94/62 |
| Purity Grade | free of RNase and DNase |
| | free of pyrogens |
| | free of PCR inhibitors |
| | free of human DNA |
| | free of endotoxins |
| | free of ATP |
| Shelf - Life | 36 months at controlled storage conditions |
| Packaging | pcs per rack: 96 |
| | rack per case: 50 |
| Storage | Storage Temperature: 2 ° C-40 ° C, humidity 40% -80% |
| | Keep clean, ventilated and out of direct sunlight |
| | 1 , , |
| | |