## Technical Datasheet

Article - No:	PG-QA-R025-01-0094 Revision: A0
Remarks	single use only
	Specification
Product name	UFPT-REF-200E-L, 300uL Pipette tips, Refull pack, Low retention
Production conditions	Class 100,000 clean room production
	No release agent is used
	Motor molding
Classification	CE/IVD
Dimensions	C 59.3±0.2 11.80±0.3 H 40.5±0.05 D 11.80±0.3 F G 45.87 47.10
Colour	Clear
Graduation	moulded rings
Nominal Capacity	1-300UL
Sterile	Yes
Material Characteristics	polypropylene(PP),premium surface
	pack:Polyethylene terephthalate(PET)
Product Characteristics	biologically inert
	physiologically harmless
	no heavy metals according to EC/94/62
Purity Grade	free of RNase and DNase
	free of pyrogens
	free of PCR inhibitors
	free of human DNA
	free of endotoxins
	free of ATP
Shelf - Life	36 months at controlled storage conditions
	pcs per rack: 96
Packaging	rack per pack: 10
Packaging	pack per case: 10
	pcs per case: 9600
Storage	Storage Temperature: 2 ° C-40 ° C, humidity 40% -80%
	Keep clean, ventilated and out of direct sunlight
	<u> </u>