## **Technical Datasheet**

Specification	
Product name  UFPT-F-10, 10uL filter tips  Class 100,000 clean room production conditions  No release agent is used  Motor molding  CE/IVD	uction
Production conditions  Class 100,000 clean room production conditions  No release agent is used  Motor molding  CE/IVD	uction
Production conditions  No release agent is used  Motor molding  CE/IVD  A 31.720.2	uction
Motor molding  Classification  CE/IVD	B √
Classification CE/IVD	B </th
D 31.7±0.2	B < □
11.3:02	B
Dimensions  + 0.6±0.05	ф3.7±0.05 ф6.0±0.06
Colour Cear	
Graduation moulded rings	
Nominal Capacity 1-10UL	
Material Characteristics polypropylene(PP),premium sur	face
filter :high density polyethylene	(PE)
biologically inert	
Product Characteristics physiologically harmless	
no heavy metals according to E	C/94/62
free of RNase and DNase	
free of pyrogens	
Purity Grade free of PCR inhibitors	
tree of numan DNA	
free of endotoxins	
free of ATP	
Shelf - Life 36 months at controlled storage	conditions
Packaging pcs per rack: 96	
rack per case: 50	
Storage Temperature: 2 ° C-40	° C, humidity 40% -80%
Keep clean, ventilated and out of	of direct sunlight