

## Technical Datasheet

<b>Article - No:</b>	PG-QA-R025-01-0064	Revision: A0
<b>Remarks</b>	single use only	
<b>Specification</b>		
<b>Product name</b>	UFPT-F-10E, 10uL filter tips	
<b>Production conditions</b>	Class 100,000 clean room production	
	No release agent is used	
	Motor molding	
<b>Classification</b>	CE/IVD	
<b>Dimensions</b>	<p>The drawing shows a side view of a filter tip with various dimensions labeled. Dimension C is the total length (45.7±0.2). Dimension D is the diameter of the main body (18±0.4). Dimension E is the diameter of the filter element (4.3±0.1). Dimension F is the diameter of the narrow neck (4.20). Dimension G is the diameter of the wide base (5.9±0.05). Dimension H is the diameter of the very narrow tip (0.6±0.05). Dimension I is the diameter of the base (0.9±0.05). Dimension L is the length of the filter element. Section lines A-A and B-B are indicated.</p>	
<b>Colour</b>	Clear	
<b>Graduation</b>	moulded rings	
<b>Nominal Capacity</b>	1-10UL	
<b>Material Characteristics</b>	polypropylene(PP),premium surface	
	filter :high density polyethylene(PE)	
<b>Product Characteristics</b>	biologically inert	
	physiologically harmless	
	no heavy metals according to EC/94/62	
<b>Purity Grade</b>	free of RNase and DNase	
	free of pyrogens	
	free of PCR inhibitors	
	free of human DNA	
	free of endotoxins	
	free of ATP	
<b>Shelf - Life</b>	36 months at controlled storage conditions	
<b>Packaging</b>	pcs per rack: 96	
	rack per case: 50	
<b>Storage</b>	Storage Temperature: 2 ° C-40 ° C, humidity 40% -80%	
	Keep clean, ventilated and out of direct sunlight	